ACQUAPAZZA APPA-GH5 System Chart

Panasonic DMW-FL70※2

LSS2(LSD Strobo System) (※2, ※3)

Spacer with a mount base | Spacer with a mount base

Acrylics window (With no finder hole)

APPA-GH5 BODY

Acrylics window (With a finder hole)

M10 Ball Joint

INON 45-Degree view finder

INON Finder Window unit

INON Straight view finder

Fish Eye

LUMIX G FISHEYE 8mm F3
100 Dome Port SB ※1, ※8
P8F Lens receiving ※5
P8F F GearSB

ED 8mm F1.8 Fisheye PRO
100 Dome Port SB ※1, ※8
O8FExtentionSB ※6
O8F F GearSB

LUMIX G VARIO 7-14mm / F4.0 ASPH.
170 Dome Port LB ※1, ※8
O714 Lens receiving ※5
MFBand A
P714 adapter ※7
P714 Extention SB ※6
P714 Z Gear SB

M.ZUIKO DIGITAL ED 7-14mm F2.8 PRO
170 Dome Port LB ※1 ※8
O714 Lens receiving ※5
MFBandA
0714 adapter SB
0714L818 Extention SB
0714 Z Gear SB

LEICA DG VARIO-ELMARIT 8-18mm/F2.8-4.0 ASPH.
170 Dome Port LB ※1 ※8
L818 Lens receiving ※5
MFBandA
0714L818Extention SB
L818 Z Gear SB

LEICA DG VARIO-ELMARIT 12-60mm/F2.8-4.0
170 Dome Port LB ※1 ※8
MFBandA
L1260 adapter SB
L1260 Extention SB ※6
L1260 Z Gear SB

LUMIX G X VARIO 12-35mm / F2.8 II
170 Dome Port LB ※1 ※8
MFBandA
L1235 adapter SB
L1235 Extention SB ※6
L1235 Z Gear SB

MARCO

LUMIX G MACRO 30mm F2.8 ASPH. MEGA O.I.S.
Flip Lens Adapter M67
P30L45M Port SB ※4
P30M Lens receiving SB ※5
P30M F Gear SB

LEICA DG MACRO-ELMARIT 45mm F2.8 ASPH. MEGA O.I.S.
Flip Lens AdapterM67
P30L45M Port SB ※4
L45M Lens receiving SB ※5
L45M F Gear SB

· SB stands for Small Bayonet.

※1 It's original dome of ACQUAPAZZA.

※2 when using an exterior strobe, it needs the genuine strobe DMW-FL70 or the LSS2.

※3 Please use your exterior strobe only after confirming that the LSS2 is working properly.

INON: D-2000 type 4; Z-240 Type 4; S-2000 SEA&SEA: YS-D1
(Proper functioning with other models has not been confirmed. Some other strobes may not be compatible.)

※4 This port is common. Only the lens receiving and the F gear are different.

※5 Required. Operation will become unstable if it does not attach.

※6 Lens receiving SB is included in the extension.

※7 It is required when using the MF band A.

※8 The shade is included.

【Standard Features】
◎Pressure tested to 100m / 328.08ft
◎Vari-angle grip
◎Safety latch
◎15 body color
◎Mount Base (Can be fitted with an adaptor to fit 4 types of couplings.)
◎M10 screws *2
◎M14/M16 accessory port
◎3 tripod screws *3
◎Trigger type shutter lever
◎The sync cord adaptor

【Optional Accessories】
◎Flip lens adaptor M67
◎Spacer with a mount base
◎M10 Ball Joint L60
◎M10 Ball Joint L80
◎LSS2
◎Premium Color Mat black (Body + Cover)
◎Premium Color Mat black (Port + Extension)

⚠ Caution — Be sure to read the instruction manual before using for your safe and correct use.

ISO 9001 JACO QC07J0070
UKAS MANAGEMENT SYSTEMS 051
MS JAB CM021